	G:\SAB\REPORTS\2000report\2000drafts\ECLTTFBR.wpd/March 28, 2000 (2:05PM
1 2	May, 2000
3	
4	EPA-SAB-DWC-COM-00
5	
6	Honorable Carol M. Browner
7	Administrator
8	U.S. Environmental Protection Agency
9	401 M Street SW
10	Washington, DC 20460
11	
12	Subject: Commentary on EPA's Draft Proposal for a Long-Term 1 Enhanced Surface
13	Water Treatment and Filter Backwash Rule
14	Dear Ms. Browner:
15	
16	The Drinking Water Committee (DWC) of the Environmental Protection Agency's (EPA)
17	Science Advisory Board (SAB) met in Washington, D.C. on March 13, 2000 to review the Agency's
18	Draft Proposal for the Long-Term 1 Enhanced Surface Water Treatment and Filter Backwash Rule
19	(LT1FBR). The rule is intended to increase protection against microbial contamination (especially
20	Cryptosporidium) in finished drinking water supplies from systems using surface water or ground
21	water under the direct influence of surface water.
22 23	The Committee conducted this review in fulfillment of its responsibilities under Section 1412(e)
24	of the Safe Drinking Water Act (SDWA as amended in August 1996) which state:
25	of the State Dilliking Water Feet (SD WF1 as tallefleed in Flagust 1996) which state.
26	The Administrator shall request comments from the Science Advisory Board
27	(established under the Environmental Research, Development, and
28	Demonstration Act of 1978) prior to proposal of a maximum contaminant level
29	goal and national primary drinking water regulation. The Board shall respond, as
30	it deems appropriate, within the time period applicable for promulgation of the
31	national primary drinking water standard concerned. This subsection shall, under
32	no circumstances, be used to delay final promulgation of any national primary
33	drinking water standard.
34	
35	EPA's draft proposal was evaluated by the Committee while it was still under review by the
36	Office of Management and Budget (OMB) and prior to being released for publication in the Federal
37	Register as a proposed rule. As such, the DWC members recognize that specific elements are subject
38	to change after the OMB review.
39	
10	The Committee reached closure on the document during the March 13-14, 2000 meeting. The
41 42	comments that the committee wishes to raise to the Administrator are included in the following sections of this letter. The Committee compliments the Agency on the significant internal efforts of EPA staff, as

well as the efforts to include Stakeholders and this Board in reviewing this rule.

One general issue was raised by members during the discussion. This is the problem that is presented to reviewers who evaluate a regulatory package, which refers to but does not include, detailed technical information on the science that supports the rulemaking. Not having specific technical information available on the issues discussed in the rule can impede the effective evaluation of important issues by the Board. Committee members noted that for future reviews, it will be important to identify and provide the relevant technical support documents that underpin Agency proposals reviewed under this SDWA requirement. Committee staff and Agency representatives should discuss such issues sufficiently in advance of the actual SAB review so that the appropriate technical documentation to support a thorough review can be identified and obtained for the Committee.

1. BACKGROUND

1.1 Statutory Context

The Safe Drinking Water Act (SDWA, 1996a) requires that EPA publish a maximum contaminant level goal [MCLG] if it determines that a drinking water contaminant may have an adverse effect on the health of persons; that the contaminant is known to occur, or there is a substantial likelihood that the contaminant will occur, in public water systems with a frequency and at levels of public health concern; and that regulation of the contaminant presents a meaningful opportunity for health risk reduction for persons served by public water systems. MCLGs are to be "set at the level at which no known or anticipated adverse effects on the health of persons occur and which allows an adequate margin of safety"(SDWA, 1996b).

EPA must publish a National Primary Drinking Water Regulation (NPDWR) that either specifies a maximum contaminant level (MCL) for such contaminants (the MCL must be set as close to the MCLG as is feasible) (SDWA, 1996c) or specify "the use of a treatment technique in lieu of establishing an [MCL]," if EPA finds "that it is not economically or technologically feasible to ascertain the level of the contaminant" (SDWA, 1996d) in water. The Act gives special meaning to the term 'feasible' noting that it "means feasible with the use of the best technology, treatment techniques, and other means [found by examination under] field conditions...are available (taking cost into consideration)" (SDWA, 1996e)

In addition, when EPA proposes such a regulation, the Administrator must also "publish a determination as to whether the benefits of the [MCL] justify, or do not justify, the costs..." (SDWA, 1996f). This determination is to be based upon a Health Risk Reduction and Cost Analysis (HRRCA); and it must "use i) the best available, peer-reviewed science and supporting studies conducted in accordance with sound and objective scientific practices; and ii) data collected by accepted methods or best available methods (if the reliability of the method and the nature of the decision justifies use of the

data)" (SDWA, 1996g); and "ensure that the presentation of information on public health effects is comprehensive, informative, and understandable" (SDWA, 1996h).

Existing actions and requirements related to the draft proposal reviewed by the Committee include EPA's Interim Enhanced Surface Water Treatment Rule (IESWTR) and a Stage 1 Disinfection Byproducts Rule (DBP1) both of which were promulgated in December, 1998. In addition, the Act requires "EPA to promulgate a Long-Term 1 Enhanced Surface Water Treatment Rule for systems serving less than 10,000 people) by November, 2000 [cited as SDWA 1412(b)(2)(C)](EPA, 2000a) and also to promulgate a regulation to govern the recycling of filter backwash water within the treatment process of a public water system by August, 2000 [cited as SDWA 1412(b)(14)]."

1.2 Provisions of the Proposal Reviewed by the Drinking Water Committee

The draft proposal applies to public water systems that use surface water, or ground water under the direct influence of surface water (EPA, 2000a). The Long Term 1 portion of the rule applies to systems having less than 10,000 persons served. Provisions of the rule address:

1) <u>Turbidity</u>: Individual filter turbidity and combined filter effluent turbidity requirements for conventional and direct filtration systems;

2) <u>Disinfection Benchmarking</u>: Public water systems must develop a disinfection profile unless they conduct applicability monitoring to demonstrate that their disinfection byproduct (DBP) levels are less than 80 percent of the maximum contaminant levels. Also, whenever systems consider making significant changes to disinfection practices, they will be required to develop a disinfection benchmark; and

3) Other Requirements: Covers will be required for finished water reservoirs completed after the rule becomes effective as will additional watershed control requirements for unfiltered systems.

The Filter Backwash portion of the rule applies to all systems which recycle irrespective of the population served (EPA, 2000a). Provisions of the rule address:

1) <u>Point of Backwash Return</u>: Requires the return of spent filter backwash water, thickener supernatant, and liquids from dewatering processes prior to the point of primary coagulant addition unless the State specifies an alternative location;

2) <u>Recycle Treatment Information</u>: Detailed recycle information must be provided to the State by direct filtration systems recycling to the treatment process. The State may require modification of the process;

Recycle Self-Assessment: Conventional systems practicing direct recycle that use 20 or fewer filters to meet production requirements during a month and recycle filter backwash water and/or gravity thickener supernatant within the treatment process must conduct a onemonth, one-time recycle self assessment (hydraulic flow monitoring and data reporting to the State).

2. SPECIFIC COMMENTS -

Key points raised by the Committee are presented below. Section 2.1 applies to the Long Term 1 Enhanced Surface Water Treatment portion of the proposal and Section 2.2 applies to the Filter Backwash portion of the proposal.

2.1 Long Term 1 Enhanced Surface Water Treatment Proposal

Turbidity Requirements - Combined Filter Effluent in Small Plants 2.1.1

Recommendation: The Science Advisory Board recommends that EPA outline further measures that it will take to ensure that the desired level of performance can be successfully achieved.

The Committee noted that it can be demonstrated that a well-designed package plant, operating within its design range and with close operator supervision, is able to meet the proposed 0.3 NTU criterion 95 per cent of the time. Experience also indicates that good operator training is important in ensuring that such goals are successfully achieved. However, it is important to recognize that operators develop advanced skills through effective training have opportunities to locate more lucrative employment with larger utilities. Given current conditions, it is difficult to imagine that small systems will be able to provide the amount of quality operator attention required to meet these regulations over the long term without some attention being given to developing an approach to provide long term training support.

32

2.1.2 Turbidity Requirements - Collection of Data by Small Systems

34 35

36

Recommendation: The SAB sees no technical problem with small utilities maintaining continuous monitoring equipment that stores and reports on turbidity data at 15 minute intervals.

37 38 39

40

41

Continuous monitoring is conducted so that the operators can maintain an awareness of each filter's performance. It is not merely an exercise to capture, catalog and report additional quantities of data. The number of data points is not really the issue. With current

programmable logic controller (PLC) technology, data storage, data analysis and data display can be accomplished easily and inexpensively. If continuous monitoring does fail, sampling every four hours is sufficient to maintain good operation until a malfunctioning recorder can be replaced.

2.2 Filter Backwash Proposal

2.2.1 Issues of where to return the backwash flow in conventional plants

Recommendation 1: The SAB recommends that EPA conduct studies to determine if gravity settling of washwater return flows is sufficient or if additional treatment is required. If studies reveal problems, then more specific requirements for treatment of backwashwater should be considered. Based on the evidence now available, the SAB recommends against requiring that washwaters be recycled ahead of the point of coagulant addition.

Many older plants with separate coagulation, sedimentation, and filtration steps return all backwash flows to a single settling basin. Experience has shown that flow equalization or better flow distribution can improve particulate removal in these situations. Here, caution should be used in considering a requirement that washwater be recycled to a point ahead of the coagulant addition point. Washwater flows are intermittent and flow pacing alone will not resolve the matter because the coagulant demand of recycled washwater flows is often very high. Many washwaters respond well to gravity sedimentation, however, no systematic cataloging is available and in some cases, such as sludge from plants involved in color removal, they may not respond so well.

Recommendation 2: Based on the information currently available, the SAB recommends against requirements which would alter the design of these direct recycle processes.

In lime softening, experience shows that recirculating sludge ahead of lime addition improves operation. In addition, in a solids contact unit, solids recirculation is often integral to the process. In either of these two cases, changes could be detrimental to these processes, which are often quite efficient in their current form.

2.2.2 Determining if a Water Treatment Plant is Exceeding Its Capacity

Recommendation: The SAB recommends that the Agency require monitoring of performance parameters, like settled water turbidity and filtered water turbidity instead of trying to determine capacity.

Capacity Parameters like filter rate and basin overflow rate can be defined with

precision, but all states do not define these capacities in the same way – particularly where recycled flows are concerned. This practice has probably survived because the effect of these capacity parameters on plant performance is not so precise. For example, although filter performance declines as the filter rate increases, the decline is gradual. A filter operating at 5.5 gpm/sf (gallons/minute/square foot) performs nearly as well as the same filter operating at 5 gpm/sf. Likewise, a horizontal settling basin operating at 1.1 gpm/sf performs nearly as well as the same basin operating at 1.0 gpm/sf. Although turbidity removal does not directly predict the removal of microorganisms, it is the only standard method the industry has today for monitoring the removal of particulates.

2.2.3 When is it Most Appropriate to Monitor?

Recommendation: The Science Advisory Board recommends that EPA require monitoring during periods of the year when unit processes are known to perform poorly instead of focusing on high periods of demand alone.

Although the month with the highest demand is the month when the plant's official capacity is most likely to be exceeded it is not necessarily the month when the plant's treatment performance will suffer the most. Usually poor treatment performance has more to do with influent water quality than any other parameter. In fact, many water treatment plants operate below their design capacity all year. Experience shows that poor quality generally occurs when algae bloom in the spring and fall, during spring runoff, or during cold temperatures in the winter. Maximum recycling occurs when poor influent water quality occurs at or near the period of maximum demand. Monitoring treatment performance is the best way to understand the impact of recycled streams on water quality.

2.2.4 Is Limiting the Self-assessment to Plants with Less Than 20 Filters Appropriate?

Recommendation: The Science Advisory Board recommends that EPA require all plants to do a self-assessment, no matter how many filters they have.

Recycled streams are more important in plants with fewer filters. Depending on design and operating conditions, this effect diminishes once the plant is large enough so that the backwash from more than one filter is being returned at the same time. On the other hand, it is difficult to justify a particular number of filters and most large plants should have no difficulty in conducting this study.

2.2.5 Requirements for Direct Filtration Plants

Recommendation: The Science Advisory Board recommends that EPA study the treatment

of recycled flows in direct filtration plants in order to determine the level of treatment that is appropriate in light of requirements for Cryptosporidium removal. It is not necessary to require treatment of recycled flows in direct filtration plants. This is because all direct filtration plants must treat their recycle stream to prevent recycling of particulates in order to meet conventional standards. Surveys which do not report a treatment step reflect a poor understanding of the process on the part of the person responding to the survey. On the other hand, treatment of recycled washwater in direct filtration plants is normally limited to some form of gravity sedimentation and the performance of a direct filtration plant is particularly sensitive to recycled flows. EPA should conduct studies to determine if that level of treatment is appropriate. 2.3 Economic Assessment 2.3.1 Estimating Illness Avoided. Recommendation: The Science Advisory Board recommends that EPA give special attention to the control of outbreaks as well as endemic disease. A number of illnesses will be avoided with appropriate criteria implemented on systems below 10,000 and appropriate recycle flow controls. On the other hand, unit process upset or failure has also caused major disease outbreaks. EPA should continue to promote the multiple barrier concept in the control of diseases and not rely on improving the performance of invididual unit processes alone. The public record on waterborne disease is dominated by these outbreaks and it will not improve if only endemic disease in reduced. We look forward to the response of the Office of Water to the advice in this letter. Sincerely, Dr. Richard J. Bull, Chair

 Drinking Water Committee

1 2 3 4	U.S. Environmental Protection Agency Science Advisory Board Drinking Water Committee (DWC) March 13-14, 2000 Meeting
5 6	Roster
7	<u>CHAIR</u>
8 9 10	DR. RICHARD BULL, Batelle Pacific Northwest Laboratories, Molecular Biosciences, P.O. Box 999-P7-56, Richland, WA
11 12	<u>MEMBERS</u>
13 14 15	Dr. DAVID B. BAKER, Heidelberg College, Water Quality Laboratory, 310 East Market Street Tiffin, OH
16 17 18 19	DR. MARY DAVIS, Professor of Pharmacology & Toxicology, Department of Pharmacology & Toxicology, Robert C. Byrd Health Sciences Center, West Virginia University, Morgantown, WV.
20 21 22	DR. RICARDO DE LEON, Principal Microbiologist, Metropolitan Water District of Southern California, Water Quality Laboratory, La Verne, CA
23 24 25	DR. YVONNE DRAGAN, Ohio State University, 1148 James CHRI, 300 W 10th Avenue, Columbus, OH
26 27 28	DR. JOHN EVANS, Director, Program in Environmental Health and Public Policy, Harvard Center for Risk Analysis, 655 Huntington Avenue, Boston, Massachusetts
29 30 31	DR. BARBARA L. HARPER, Toxicologist, Yakama Indian Nation, Richland, WA
32 33	DR. CHRISTINE MOE, Assistant Professor, Department of Epidemiology. University of North Carolina, Chapel Hill, NC
34 35 36	DR. LEE D. (L.D.) MCMULLEN, General Manager, Des Moines Water Works, 2201 Valley Drive, Des Moines, IA
37 38 39	DR. CHARLES O'MELIA, Professor and Chairman, Department of Geography and Environmental Engineering, The Johns Hopkins University, Baltimore, MD
10 11 12	DR. GARY A. TORANZOS, Associate Professor, Department of Biology, University of Puerto Rico, San Juan, Puerto Rico
13 14 15	DR. RHODES TRUSSELL, Montgomery Watson, 300 North Lake Avenue, Suite 1200, Pasadena, CA

NOTICE

2	
2	

This report has been written as part of the activities of the Science Advisory Board, a public advisory group providing extramural scientific information and advice to the Administrator and other officials of the Environmental Protection Agency. The Board is structured to provide balanced, expert assessment of scientific matters related to problems facing the Agency. This report has not been reviewed for approval by the Agency and, hence, the contents of this report do not necessarily represent the views and policies of the Environmental Protection Agency, nor of other agencies in the Executive Branch of the Federal government, nor does mention of trade names or commercial products constitute a recommendation for use.

Distribution and Availability: This Science Advisory Board report is provided to the EPA

APPENDIX A - I
copies and further information are available from the SAB Staff.
provided in the SAB's monthly newsletter (Happenings at the Science Advisory Board). Additional
public, and is posted on the SAB website (www.epa.gov/sab). Information on its availability is also
Administrator, senior Agency management, appropriate program staff, interested members of the

A - 1

1	REFERENCES
2	
3	EPA (2000a) Long Term 1 Enhanced Surface Water Treatment and Filter Backwash Rule - Fact
4	Sheet. Fact Sheet developed by US EPA Office of Water for the Science Advisory Board
5	Briefing. February 14, 2000.
6	
7	SDWA (1996). Safe Drinking Water Act as Amended. August 6, 1996. National Drinking Water
8	Regulations. Code of Federal Regulations. Title XIV. Sections 1400 et seq. Congress of the
9	United States. Sections as noted below:
10	
11	(1996a): Section 1412(b)(1)(A) General Authority.
12	(1996b): Section 1412(b)(4)(A) MCLGs
13	(1996c): Section 1412(b)(4)(B) MCLs
14	(1996d): Section 1412(b)(7)(A) Treatment Technology
15	(1996e): Section 1412(b)(4)(D) Feasible
16	(1996f): Section 1412(b)(4)(C) B-C Justification
17	(1996g): Section 1412(b)(3)(A) Best Science
18	(1996h): Section 1412(b)(3)(B) Public Information
19	(1996i): Section 1412(b)(3)(C) HRRCA
20	
21	
22	
23	
24	
25	
26	
27 28	
29	
30	
31	
32	
33	
34	
35	
36	
37	
38	
39	